



WS 620XT



SPECIFICATIONS

Acoustical specifications

FREQUENCY RESPONSE (-10DB):
70 Hz ÷ 20000 Hz

MAX SPL @ 1M:
105 dB

COVERAGE ANGLE:
120°

SYSTEM SENSITIVITY:
91 dB

Power section

NOMINAL IMPEDANCE:
4 ohm

POWER HANDLING:
12 W RMS

PEAK POWER HANDLING:
48 W PEAK

RECOMMENDED AMPLIFIER:
24 W

Transducers

DOME TWEETER:
1.0"

WOOFER:
Coaxial 6.0"

Input/Output section

INPUT CONNECTORS:
Screw Terminals

OUTPUT CONNECTORS:
Screw Terminals

POWER SELECTION 1 (100 V):
12 W - 833 ohm

POWER SELECTION 2 (100 V):
6 W - 1667 ohm

POWER SELECTION 3 (100 V):
3 W - 3333 ohm

Standard compliance

IP PROTECTION GRADE:
IP 55

CE MARKING:
Yes

Physical specifications

CABINET/CASE MATERIAL:
Plastic

GRILLE:
Plastic

COLOR:
White - RAL 9016



SPECSHEET

Size

DEPTH:
115 mm / 4.53 inches

RECESSED DEPTH:
97 mm / 3.82 inches

DIAMETER:
165 mm / 6.5 inches

WEIGHT:
0.66 kg / 1.46 lbs

Shipping informations

PACKAGE HEIGHT:
155 mm / 6.1 inches

PACKAGE WIDTH:
195 mm / 7.68 inches

PACKAGE DEPTH:
190 mm / 7.48 inches

PACKAGE WEIGHT:
1.58 kg / 3.48 lbs

PART NUMBERS:

• 13133044
WS 620XT

EAN 8024530004996