



PRODUCT DESCRIPTION

REF.	DESCRIPTION	UNITS
	<u>Restaurant</u>	
60252	In-Ceiling Wi-Fi SOUNDAROUND Amplifier	1
	The In-Ceiling Wi-Fi SOUNDAROUND Amplifier will provide a Multiuser - Multiroom Audio solution, powered by QUALCOMM technology. Device with 2 audio sources: WIFI streaming and AUDIO-IN. Each In-Wall Audio Control unit has a UNIQUE identifier to be able to distinguish between them when several units are connected to the same network. This ID can be customized by the user. The Control unit also has an ETHERNET connector for hardwired installations. AUDIO-IN: 3,5mm jack audio input to connect any external audio source. POWER-IN: input for external power supply, 24Vdc/15Vdc/12Vdc allowed. SPEAKER OUTPUT: terminals for right and left speakers connections. 8 ohms speakers permitted. Audio power output up to 25+25W.	
11396	60W Power Supply (15Vdc output)	1
	60W Power Supply. 120/230Vac, 15Vdc. Recommended for installations of SOUNDAROUND Controller to up to four 8ohm speakers and up to eight 16ohm speakers. Max audio output 16+16W.	
16602	5" Two way design Loudspeaker 16Ω	6
	5" two-way coaxial loudspeaker, 16 Ohms. With 5" woofer and 3/4" tweeter. 10W/20W maximum allowable power. SPL (1W/1m) 88 dB. Speaker grille and ring in aluminum. Easy, fast and sure installation in false ceilings. Connect to screw-in terminals.	