



MEDICAL CENTER - PUBLIC ADDRESS SYSTEM

PRODUCT DESCRIPTION

REF.	DESCRIPTION	UNITS
	<u>1. 100V Main Control</u>	
91211	PR 4093 Mix Amplifier	4
	PR 4093 has been designed to provide a flexible solution for paging and music application in PA systems. It offers 6 balanced inputs mic/line with PHANTOM facility, the first of them with priority triggered by VOX circuit. In addition, 3 stereo input on RCA connectors are available. Outputs offer different functionalities, included tone control on front panel, dedicated mixing of inputs 1-6 e connection to recording devices	
81383	Power Amplifier - MPU-6412	1
	4 channel booster amplifier designed for up to 4 zone application. Equipped with XLR and jack output for connecting to another amplifier. 4 output 70V/100V/8 ohm, S/N 86 db. 3U rack 19". Dimensions: 132 x 425 x 420 mm.	
81436	Rack cabinet 31GTM9F5	1
	Rack cabinet 31GTM9F5 19" Rack cabinet 9U F550 2 bodies.	
81443	Blind panel 19" 2U	1
81445	Screw fix + M6 cage nut	50
	<u>2. Microphones</u>	
81168	DM-333D Desktop Microphone	4
	Desk base with ON/OFF switch, flexible gooseneck with cardioid dynamic microphone. Cable with male XLR connector and 2 conductors for priority activation (ding-dong).	
	<u>3. Waiting areas (GP, Dentist, Pediatrics, Midwife)</u>	
81594	100 V Loudspeaker HIT-402	14
	Two-way in-ceiling speaker 4". Power 20W 8 ohm, 1.5 /3/6 W with 100V line transformer. Dimensions: diameter 176mm x 66 depth. Minimum diameter cavity: 146 mm.	