



PRODUCT DESCRIPTION

REF.	DESCRIPTION	UNITS
	<u>1. Public Address Main Control</u>	
91211	Mixer Amplifier PR4093	1
	PR 4093 has been designed to provide a flexible solution for paging and music application in PA systems. It offers 6 balanced inputs mic/line with PHANTOM facility, the first of them with priority triggered by VOX circuit. In addition, 3 stereo input on RCA connectors are available. Outputs offer different functionalities, included tone control on front panel, dedicated mixing of inputs 1-6 e connection to recording devices.	
81382	Power Amplifier MPU-6424	1
	2 channel booster amplifier designed for 2 zone application. Equipped with XLR and jack output for connecting to another amplifier. 2 output 70V/100V/8 ohm, S/N 86 db. 2U rack 19".	
81436	19" Rack cabinet 9U F550 2 bodies.	1
81443	Blind panel 19" 2U	1
81445	Screw fix + M6 cage nut	50
	<u>2. Microphones</u>	
91208	Wireless hand-held microphone	1
	Wireless microphone 2000 series has 16 individual channels. The channels are selected manually at the transmitter and receiver. The system can work with up to 6 channels at the same time. Includes male-female XLR cable.	
91209	Wireless lavalier microphone	1
	UHF wireless microphone 2000 series has 16 individual channels. The channels are selected manually at the transmitter and receiver. The system can work with up to 6 channels at the same time. Includes male-female XLR cable.	
81168	Microphone with base desktop DM-333D	1
	Desk base with ON/OFF switch, flexible gooseneck with cardioid dynamic microphone. Cable with male XLR connector and 2 conductors for priority activation (ding-dong).	
	<u>3. Corridors, Changing rooms and Toilets</u>	
81594	100 V Loudspeaker HIT-402	25

	Two-way in-ceiling speaker 4". Power 20W 8 ohm, 1.5 / 3/6 W with 100V line transformer.	
81969	100 V Loudspeaker ECS-650T	15
	Surface design mount speaker in ABS for wall or in-ceiling speaker dual cone 6.5" 2.5/5/10W 100V 80Hz-18KHz frequency response, 93dB SPL.	
	<u>4. Central Court</u>	
81995	PAIR speakers EWS-30B Black	4
	Two-way ABS speaker bass reflex black color. Woofer 5 "and 1" tweeter. 3.75/7.5/15/30W 100V and 8 ohms, frequency response: 90Hz-20KHz, sensitivity 88 dB. Dimensions: 255 x 178 x 155mm. Support included. (2 units -Pair).	
	<u>5. Press room</u>	
91203	Desk base microphone AC501DK	1
	AC 501DK is a desktop microphone base with input and output XLR connectors. It offers three different functional modalities: LOCK (bistable on/off button); TALK (microphone open with button pressed only); MUTE (mute active with button pressed). For use with MC 5054 microphone and cable 81231	
91204	Electrec microphone MC5054	1
	Condenser microphone with high quality capsule, mounted on a flexible arm 445 mm long, and to be installed on microphone support with XLR connector. It is powered with phantom from 9 V to 52 V and windshield polyurethane foam.	
81231	Microphone cable (5m)	1
81376	Mixer Amplifier 60W MA-1606	
	Mixer amplifier designed for total 6 inputs (channel) application. Included 3 AUX and up to 5 microphone connectors. The series include the models of output power 60W. Chime function (ding-dong). Dimensions: 88 x 425 x 305 mm	
81993	PAIR speakers EWS-15B black	1
	Two-way ABS Speaker bass reflex in black color. Woofer 4 "and 1" tweeter. 2.5/5/10/20W 100V and 8 ohms, frequency response: 90Hz-20KHz, sensitivity 87 dB. Dimensions: 220 x 150 x 135mm. Support included. 2 units -Pair.	